



Research Article

Optimization Strategy for Reducing CO₂ in Livestock Farming with IoT Integration and Decision Support System Approach Using Linear Programming

Annisa Fikria Shimbun^{1,*}, Muhammad Arif Alfian², Agam Saka Jati³, Edi Faizal³

¹ Universitas Cendekia Mitra Indonesia, Yogyakarta 55172, Indonesia, niesashimbun@unicimi.ac.id

² Universitas Cendekia Mitra Indonesia, Yogyakarta 55172, Indonesia, iyan2x@gmail.com

³ Universitas Cendekia Mitra Indonesia, Yogyakarta 55172, Indonesia, agam@unicimi.ac.id

⁴ Universitas Teknologi Digital Indonesia, Yogyakarta 55198, Indonesia, edifaizal@utdi.ac.id

Correspondence should be addressed to Annisa Fikria Shimbun; niesashimbun@unicimi.ac.id

Received 10 November 2024; Accepted 27 March 2025; Published 31 March 2025

© Authors 2025. CC BY-NC 4.0 (non-commercial use with attribution, indicate changes).

License: <https://creativecommons.org/licenses/by-nc/4.0/> — Published by Indonesian Journal of Data and Science.

Abstract:

Introduction: Livestock waste mismanagement contributes significantly to CO₂ emissions, adversely affecting animal health and environmental sustainability. This study aims to develop an optimization strategy for reducing CO₂ levels in livestock environments through the integration of Internet of Things (IoT) technology and a Decision Support System (DSS) using Linear Programming. **Methods:** IoT sensors were deployed to monitor environmental parameters such as CO₂ levels, temperature, and humidity in real time. A Linear Programming (LP) model was formulated to determine the optimal frequency of two CO₂-reducing actions: spraying Effective Microorganisms (EM4) and performing waste dredging. The objective was to maximize CO₂ reduction under cost and time constraints. The model iteratively updated its parameters based on sensor data feedback, ensuring dynamic and adaptive optimization. **Results:** Simulation results indicated that the LP model successfully identified optimal actions within predefined constraints. The optimal strategy was spraying EM4 eight times over eight days, achieving a CO₂ reduction of 800 ppm with a total cost of Rp 400,000—within the Rp 500,000 budget limit and 8-hour duration constraint. Validation through simulation confirmed the model's accuracy, with prediction deviations consistently falling within an acceptable threshold (± 20 ppm). **Conclusions:** The integration of IoT with an LP-based DSS offers a practical and efficient solution for CO₂ reduction in livestock farming. This system enhances decision-making for environmental management, demonstrating potential for scalable application in sustainable agriculture. Future work should incorporate more environmental variables and broader validation to improve model generalizability and precision.

Keywords: Decision Support System, IoT, Linear Programming, Livestock Waste, Optimization of CO₂ Reduction.

1. Introduction

The management of livestock environments poses its own challenges, especially in maintaining air quality that can affect livestock health and environmental sustainability. CO₂ emissions that pollute the atmosphere can disrupt the lives of humans, plants, and animals. The presence of emission gases in the atmosphere shows a significant relationship between environmental pollution and human health [1]. CO₂ emissions from livestock waste are often a cause of declining air quality. Livestock greenhouse gas (GHG) emissions by region show that Asia produces the most, followed by Latin America and the Caribbean, Europe, North America, Africa, and Oceania [2]. Environmental conditions in livestock farming that affect the health and stress levels of livestock include CO₂ levels, humidity, and temperature. Therefore, an innovative approach is needed to keep CO₂ levels in livestock farms below the permissible CO₂ threshold [3], [4].

Internet of Things (IoT) technology has opened new opportunities for real-time monitoring of livestock environments, especially CO₂ levels, humidity, and temperature conditions through continuous IoT sensors to support decision-making [5]–[8]. These factors are considered because livestock stress levels, among others, depend on temperature and humidity. The impact of heat stress on livestock can be categorized into feed nutrient

use, feed intake, livestock production, reproduction, health, and death. In addition, integration with the Decision Support System (DSS) [9], [10] approach enables optimization in determining the frequency of spraying Effective Microorganisms (EM4) solution or waste dredging to optimize CO₂ reduction [11]–[14]. Composting can be an effective method for reducing greenhouse gas (GHG) emissions from various waste materials, including animal manure.

Theoretically, this research adds to the literature on the application of the Internet of Things (IoT) in the efficiency of livestock environment management by optimizing CO₂ reduction in livestock farms. Additionally, by developing a Linear Programming-based Decision Support System (DSS) model, it can support more efficient CO₂ reduction optimization by utilizing real-time data from IoT sensors. This approach is also based on previous studies that applied quantitative methods in decision support systems. For instance, the study “Community Decision Support Service System Village Level Mandiri Based On An Interactive Website” [15] utilized a web-based system to support community decision-making based on real-time information.

This research adopts similar principles by applying Linear Programming (LP) in Decision Support Systems (DSS) to determine optimal strategies for IoT-based livestock waste management [16]–[19]. By combining real-time monitoring through sensors with an LP-based optimization model, this system can provide more precise and efficient action recommendations compared to conventional methods [20], [21]. The practical contribution of this research is the development of a model that determines the optimal strategy between spraying Effective Microorganisms (EM4) solution and waste dredging. This model can help provide solutions for more efficient organic waste management to optimize CO₂ reduction, thereby creating a healthier environment for livestock and their surroundings.

2. Method:

This research uses a quantitative approach with an experimental design to test the effectiveness of integrating IoT technology and Linear Programming (LP)-based DSS in optimizing CO₂ reduction [22], [23]. The objective function of this LP method is to maximize the reduction of CO₂ concentration (ppm). The LP model is used to determine the optimal actions based on cost and time constraints, with the objective function of maximizing CO₂ reduction through two methods: spraying and waste dredging. Here is the flowchart that illustrates the optimization process based on IoT and Linear Programming (LP) for decision-making in environmental management [24]–[26]. The sequence begins with sensor data collection, processing with the LP model, result verification, and corrective actions if the results are not optimal. Once the actions are implemented, new data is collected for continuous improvement.




Figure 1. Flowchart of the optimization process based on IoT and LP-based DSS for livestock waste management

Formulation of the Linear Programming Model

The objective function is to optimize CO₂ reduction.

$$Z = 100X_1 + 400X_2$$

Where: X_1 = is the frequency of spraying

X_2 = is the frequency of dredging

Constraints:

- 1) $50.000 X_1 + 300.000 X_2 \leq 500.000$ (Cost Constraints)
- 2) $1 X_1 + 5 X_2 \leq 8$ (Duration Constraints)
- 3) $X_1 \geq 0; X_2 \geq 0$ (Non-Negativity Constraints)

The following are the process flow steps for the integration of IoT and LP-based DSS:




Figure 2. Flow of IoT Sensor Integration and LP Model for Optimizing Spraying & Dredging Frequency

- a. Initial Data Collection from IoT
IoT sensors measure data such as CO₂ levels, humidity, and ambient temperature. This data is transmitted to a central system for processing.
- b. Input Data into the LP Model
Based on the received CO₂ data, the system processes the LP model to determine the optimal action. For example, the LP results might suggest spraying 8 times to achieve a CO₂ reduction target of 800 ppm.
- c. Action Implementation
The spraying is carried out 8 times in the field as recommended by the LP model. During each spraying session, CO₂ levels are monitored to assess the effectiveness of the action.
- d. Effectiveness Measurement of Actions
After the actions are completed, IoT monitors CO₂ levels again to ensure the target (800 ppm) is achieved. The possible outcomes are as follows:
Achieved: If the CO₂ reduction target is met (800 ppm from 8 sprays), the formula $Z=100x_1+400x_2$ can be used without changes in the next iteration.
Not Achieved: If the CO₂ reduction is below the target, the data is reanalyzed.
- e. Adjustment of Action Efficiency
If the average reduction per spray turns out to be greater or smaller than the initial estimate (100 ppm per spray), this data is used to update the parameters for improved accuracy:
For example, if the reduction from 8 sprays is only 600 ppm, the average reduction per spray would be 75 ppm instead of 100 ppm. The LP formula is then updated based on the actual data:
New Formula: $Z = 75x_1 + 400x_2$, where x_1 is adjusted to reflect the actual results.
- f. Continuous Iteration
Data from the actions performed is sent to the system for evaluation. The LP model recalculates using the new data to determine the next optimal actions. This process is carried out continuously every month or according to the planned evaluation cycle.
- g. System Validation and Improvement
The system periodically performs validation to ensure that the formulas and LP parameters remain relevant to actual field conditions. If significant discrepancies are found between actual results and predictions, the LP parameters are updated and dynamically adjusted based on IoT data.

Linear Programming Modeling

The objective function with this LP method is to optimize the value of CO₂ concentration reduction (ppm). Actions to reduce CO₂ concentration (ppm) values are through spraying and dredging. Each time spraying costs Rp 50,000 and takes 1 hour, whereas each time dredging costs Rp 300,000 and takes 5 hours to complete. The constraints for the action cost are Rp 500,000 and for the duration are 8 hours.

Each time spraying can reduce CO₂ concentration by 100 ppm, whereas each time dredging can reduce CO₂ concentration by 400 ppm.

Objective Function:

$$Z = 100X_1 + 400X_2$$

Where:

X_1 = is the frequency of spraying

X_2 = is the frequency of dredging

Z = Total CO₂ Reduction

Constraint Function:

- $50.000 X_1 + 300.000 X_2 \leq 500.000$ (Cost Constraints)
- $1 X_1 + 5 X_2 \leq 8$ (Duration Constraints)
- $X_1 \geq 0; X_2 \geq 0$ (Non-Negativity Constraints)

Illustrate All Constraints to Determine the Feasible Solution Space

1) Cost Contains

The equation $50,000 X_1 + 300,000 X_2 \leq 500,000$ can be transformed into the equation:

$$50,000 X_1 + 300,000 X_2 = 500,000.$$

To make it easier to draw constraint lines, determine two opposite points.

From the equation: $50,000 X_1 + 300,000 X_2 = 500,000$

If $X_1 = 0 \rightarrow 50.000 (0) + 300.000 X_2 = 500.000$

$$0 + 300.000 X_2 = 500.000 \rightarrow X_2 = 500.000/300.000 = 1,67$$

If $X_2 = 0 \rightarrow 50.000 X_1 + 300.000 (0) = 500.000$

$$50.000 X_1 + 0 = 500.000 \rightarrow X_1 = 500.000/50.000 = 10$$

The Drawing of the Objective Function Line from the Cost Constraints:

$$X \rightarrow 50.000X_1 + 300.000X_2 = 500.000$$




Figure 3. Objective Function Line for Cost Constraint

2) Duration Contains

The equation $1X_1 + 5X_2 \leq 8$ can be transformed into the equation: $1X_1 + 5X_2 = 8$

To make it easier to draw constraint lines, determine two opposite points.

From the equation: $1X_1 + 5X_2 = 8$

If $X_1 = 0 \rightarrow 1X_1 + 5X_2 = 8$

$$0 + 5X_2 = 8 \rightarrow X_2 = \frac{8}{5} = 1,60$$

If $X_2 = 0 \rightarrow 1X_1 + 5X_2 = 8$

$$1X_1 + 5(0) = 8 \rightarrow X_1 = \frac{8}{1} = 8$$

The Drawing of the Objective Function Line from the Duration Constraints:




Figure 4. Objective Function Line for Time Constraint

3) The feasible set area is the area encompassed by the cost and duration constraints, which includes point A, B, and C.




Figure 5. Feasible Set Area

Finding the Value of Z from Each Extreme Point

The feasible area includes area ABC

a. Point A:

Coordinates of Point A (0;0) → X1 = 0; X2 = 0

Maximization Z = 100X1 + 400X2

$$100(0) + 400(0) = 0$$

b. Point B:

Coordinates of Point B (8;0) → X1 = 8; X2 = 0

Maximization Z = 100X1 + 400X2

$$100(8) + 400(0) = 800$$

c. Point C:

Coordinates of Point C (0;1,60) → X1 = 0; X2 = 1,60

Maximization Z = 100(0) + 400(1,60)

$$0 + 640 = 640$$

Obtaining the Optimal Solution

Table 1. Solution Results Table

Extreme Points	Spraying Frequency (X1)	Dredging Frequency (X2)	Efficient CO ₂ Reduction Optimization Max Z = 100X1 + 400X2
A	0	0	0
B	8	0	800
C	0	1,60	640

Based on calculations from the Linear Programming model, spraying 8 times can reduce CO₂ emissions by 800 ppm. With an operational cost of 400,000 rupiah, this cost remains within the allocated budget.

This solution demonstrates the optimal allocation of resources in determining actions and frequencies needed to maximize CO₂ reduction (800 ppm). Spraying appears to be more suitable for short-term use under the given constraints, providing an efficient and practical approach within budget and time limitations.

Validation with Simulation Data

Validation of LP Model When Recommendations Align with CO₂ Emission Reduction Targets

Definition of Validation:

- CO₂ Reduction Target (8 Days): 800 ppm
- LP Prediction: 100 ppm per spray ($Z=100X_1Z = 100X_1Z=100X_1$)
- Validation Threshold: The acceptable range of deviation is within (-20) to 20 ppm from the target.
- Validation Condition: The Linear Programming model is considered valid if the actual CO₂ reduction falls within the range of 780 ppm to 820 ppm.

Calculate the Difference Between Actual and Target.

Table 2. Spraying Actions Table

Day	Spraying Frequency (X1)	Prediction of CO ₂ Reduction (LP) (Z=100X1)	Actual CO ₂ Reduction	Difference (Prediction - Actual)	Validation (✓ if within -20 to 20)
1	1	100	80	20	✓ Valid
2	1	100	90	10	✓ Valid
3	1	100	95	5	✓ Valid
4	1	100	95	5	✓ Valid
5	1	100	90	10	✓ Valid
6	1	100	100	0	✓ Valid
7	1	100	100	0	✓ Valid
8	1	100	110	-10	✓ Valid

Validation Analysis

- ✓ All days meet the validation criteria.
- ✓ The difference between the LP prediction and the actual results remains within the safe range (-20 to 20 ppm).
- ✓ The initial LP model is deemed valid without requiring revision.

Validation of the LP Model by determining the LP improvement method if the recommended actions do not align with the target results

When the CO₂ emission reduction does not meet the target, recommendations for improved LP methods are provided to suggest better actions. Here is the simulation data for the LP recommendations:

The initial CO₂ level is 1000 ppm (the maximum threshold). After applying the LP method, but failing to meet the target CO₂ emission reduction, recommendations for improved LP methods are created to align with the results of the actual CO₂ reduction.

Table 3. Simulation of Adjusted LP Based on CO₂ Reduction After Recommended Actions

Case	Spraying Frequency (X1)	Dredging Frequency (X2)	CO ₂ Reduction in the LP Model (ppm)	Actual CO ₂ Reduction (ppm)	Y Difference	New LP
1	8	0	800	600	1000 - 600 = 400	Z' = 75X1 + 400X2

Case	Spraying Frequency (X1)	Dredging Frequency (X2)	CO ₂ Reduction in the LP Model (ppm)	Actual CO ₂ Reduction (ppm)	Y Difference	New LP
2	6	1	700	650	1000 - 650 = 350	Z' = 87,5X1 + 400X2
3	4	2	600	500	1000 - 500 = 500	Z' = 100X1 + 400X2

Because there has been no prior research directly linking IoT and LP to optimize CO₂ reduction in farming, this study provides a novel contribution to the field. Additionally, further testing is required to confirm its reliability under various conditions. The developed model still needs to be validated with real-world data to ensure its applicability on a larger scale or in diverse environmental settings.

This optimization system modeling, based on Linear Programming (LP), integrates real-time input data from IoT devices into the system. The system then performs LP calculations to determine (X₁) (spraying frequency) and (X₂) (dredging frequency) optimally. The system can be designed to update results whenever there are changes in field conditions

3. Results and Discussion

The simulation results indicate that this method can optimally allocate resources while considering cost and time constraints. Spraying 8 times over 8 days successfully reduces CO₂ levels by 800 ppm, with the total cost remaining within the specified budget limits. Based on the results of the Linear Programming calculations, spraying 8 times meets all the cost and duration constraints. Dredging is not required because it costs too much to meet the same constraints. The total cost incurred is Rp400,000, which is below the limit of Rp500,000, with a total usage time of 8 hours, which is within the maximum limit. The solution shows the best resource allocation in determining actions and the required frequency to maximize CO₂ reduction (800 ppm). Spraying is more suitable for short-term use under such constraint conditions.

4. Conclusion

The installed IoT (Internet of Things) technology is used to monitor CO₂ levels, humidity, and temperature in real-time, with the data being automatically integrated into the data management system through the IoT Gateway. This research contributes to the efficiency of livestock environmental management by integrating Internet of Things (IoT) technology and Linear Programming (LP) methods to optimize CO₂ emission reduction. The IoT-LP concept applied in this study offers an innovative solution for reducing greenhouse gas emissions on farms, while simultaneously supporting more sustainable and efficient livestock practices. The model can also assist farm owners in making data-driven decisions to control air quality more effectively

The use of IoT technology in this research is still at a basic stage, so further development is highly recommended to integrate more environmental parameters. The hope is that these findings can become one of the alternatives for optimizing CO₂ reduction in livestock farming while aligning with the general principles of resource optimization and the use of IoT technology that has proven successful in other sectors, such as smart agriculture and industrial management.

In future research, real data from different livestock environments and a larger number of livestock can be used. This is to ensure that the developed optimization model can indeed be applied to real situations. Additionally, the next research can add more environmental parameters such as ammonia (NH₃) levels or other relevant parameters. Recommendations for future research related to IoT technology include implementing more diverse and accurate IoT sensors, and potentially developing the use of big data technology to analyze patterns of CO₂ emission changes over time. With more comprehensive follow-up research, this model has the potential to become a new standard in livestock environmental management, helping to reduce environmental impacts while improving operational efficiency and farm sustainability.

References:

- [1] Y. M. Amouzouvi *et al.*, "Evaluation of Pollutants Along the National Road N2 in Togo using the AERMOD Dispersion Model," *J. Heal. Pollut.*, vol. 10, no. 27, Sep. 2020, doi: [10.5696/2156-9614-10.27.200908](https://doi.org/10.5696/2156-9614-10.27.200908).
- [2] P. J. Gerber *et al.*, "Technical options for the mitigation of direct methane and nitrous oxide emissions from livestock: a review," *Animal*, vol. 7, pp. 220–234, 2013, doi: [10.1017/S1751731113000876](https://doi.org/10.1017/S1751731113000876).
- [3] S. Tisocco, "Integration of anaerobic co-digestion of grass silage and cattle slurry within a livestock farming

- system in Ireland: Quantification of greenhouse gas emission reduction and nutrient flow,” *Resour. Conserv. Recycl.*, vol. 206, 2024, doi: [10.1016/j.resconrec.2024.107650](https://doi.org/10.1016/j.resconrec.2024.107650).
- [4] V. Aguerre, “Co-innovation and farm technical assistance to contribute to a sustainability transition of livestock farming in Uruguay,” *Rev. Econ. e Sociol. Rural.*, vol. 62, no. 4, 2024, doi: [10.1590/1806-9479.2023.279500EN](https://doi.org/10.1590/1806-9479.2023.279500EN).
- [5] Y. Syamala, “AgriTech Revolution: The Integration of IoT in Modern Farming Solutions,” *Proceedings of 5th International Conference on IoT Based Control Networks and Intelligent Systems, ICICNIS 2024*. pp. 361–367, 2024, doi: [10.1109/ICICNIS64247.2024.10823204](https://doi.org/10.1109/ICICNIS64247.2024.10823204).
- [6] Sneha, “Smart Farming Solutions: Unveiling the Power of Cloud-IoT Integration,” *Integration of Cloud Computing and IoT: Trends, Case Studies and Applications*. pp. 157–170, 2024, doi: [10.1201/9781032656694-8](https://doi.org/10.1201/9781032656694-8).
- [7] A. Aurasopon, “Integration of IoT Technology in Hydroponic Systems for Enhanced Efficiency and Productivity in Small-Scale Farming,” *Acta Technol. Agric.*, vol. 27, no. 4, pp. 203–211, 2024, doi: [10.2478/ata-2024-0027](https://doi.org/10.2478/ata-2024-0027).
- [8] N. F. Ismail, “Internet of Things (IoT) Integration in Horizontal Farming,” *2024 IEEE International Conference on Automatic Control and Intelligent Systems, I2CACIS 2024 - Proceedings*. pp. 330–333, 2024, doi: [10.1109/I2CACIS61270.2024.10649630](https://doi.org/10.1109/I2CACIS61270.2024.10649630).
- [9] M. A. Abid, “IoT-Based Smart Biofloc Monitoring System for Fish Farming Using Machine Learning,” *IEEE Access*, vol. 12, pp. 86333–86345, 2024, doi: [10.1109/ACCESS.2024.3384263](https://doi.org/10.1109/ACCESS.2024.3384263).
- [10] N. R. P, “Optimizing Brackishwater Shrimp Farming with IoT-Enabled Water Quality Monitoring and Decision Support System,” *Thalassas*, vol. 40, no. 1, pp. 101–113, 2024, doi: [10.1007/s41208-023-00630-w](https://doi.org/10.1007/s41208-023-00630-w).
- [11] V. Aguerre, “Co-innovation and socio-technological niche development: The case of livestock farming on natural grassland in Uruguay,” *J. Rural Stud.*, vol. 97, pp. 81–94, 2023, doi: [10.1016/j.jrurstud.2022.12.003](https://doi.org/10.1016/j.jrurstud.2022.12.003).
- [12] J. Schulz, “Analysis of fluoroquinolones in dusts from intensive livestock farming and the co-occurrence of fluoroquinolone-resistant *Escherichia coli*,” *Sci. Rep.*, vol. 9, no. 1, 2019, doi: [10.1038/s41598-019-41528-z](https://doi.org/10.1038/s41598-019-41528-z).
- [13] M. A. Uranga-Soto, “Optimizing feedstock mixtures of livestock farming wastes to enhance methane yield in biogas production by co-digestion,” *J. Renew. Sustain. Energy*, vol. 10, no. 5, 2018, doi: [10.1063/1.5024524](https://doi.org/10.1063/1.5024524).
- [14] M. M. Albicette, “Co-innovation in family-farming livestock systems in rocha, Uruguay: A 3-year learning process,” *Outlook Agric.*, vol. 46, no. 2, pp. 92–98, 2017, doi: [10.1177/0030727017707407](https://doi.org/10.1177/0030727017707407).
- [15] A. Y. Nugroho, A. F. Shimbun, and N. Rohman, “Community Decision Support Service System Village Level Mandiri Based On An Interactive Website,” *Innov. J. Soc. Sci. Res.*, vol. 4, no. 4, 2024, doi: [10.31004/innovative.v4i4.13760](https://doi.org/10.31004/innovative.v4i4.13760).
- [16] A. N. Fajar, “Designing IoT urban farming monitoring systems for supporting smart farming,” *AIP Conference Proceedings*, vol. 2927, no. 1. 2024, doi: [10.1063/5.0205234](https://doi.org/10.1063/5.0205234).
- [17] I. Moutsinas, “Use of the AgroNIT smart-farming IoT ecosystem to support irrigation management and assess its impact on fruit trees’ economy and nutrition in Greece,” *Acta Horticulturae*, vol. 1, no. 1409. pp. 417–426, 2024, doi: [10.17660/ActaHortic.2024.1409.53](https://doi.org/10.17660/ActaHortic.2024.1409.53).
- [18] A. Jamwal, “Agriculture Monitoring System Using IoT and ML Smart and Improved Farming,” *2024 International Conference on Advances in Computing Research on Science Engineering and Technology, ACROSET 2024*. 2024, doi: [10.1109/ACROSET62108.2024.10743334](https://doi.org/10.1109/ACROSET62108.2024.10743334).
- [19] P. R. Yesankar, “A Review on the Role of IoT in Smart Agriculture with Reference to Efficiency, Sustainability and Precision Farming,” *5th International Conference on Electronics and Sustainable Communication Systems, ICESC 2024 - Proceedings*. pp. 533–537, 2024, doi: [10.1109/ICESC60852.2024.10689999](https://doi.org/10.1109/ICESC60852.2024.10689999).
- [20] A. Ankitha, “Sustainable Farming Through IOT-Enhanced Weather Monitoring,” *2024 IEEE International Conference on Information Technology, Electronics and Intelligent Communication Systems, ICITEICS 2024*. 2024, doi: [10.1109/ICITEICS61368.2024.10625117](https://doi.org/10.1109/ICITEICS61368.2024.10625117).
- [21] S. Kundu, “The Survey on IoT based kit for smart farming,” *Proceedings - 2024 6th International*

Conference on Computational Intelligence and Communication Technologies, CCICT 2024. pp. 114–119, 2024, doi: [10.1109/CCICT62777.2024.00030](https://doi.org/10.1109/CCICT62777.2024.00030).

- [22] X. Wang, “A freight integer linear programming model under fog computing and its application in the optimization of vehicle networking deployment,” *PLoS ONE*, vol. 15, no. 9. 2020, doi: [10.1371/journal.pone.0239628](https://doi.org/10.1371/journal.pone.0239628).
- [23] B. N. Alhasnawi, “A new communication platform for smart EMS using a mixed-integer-linear-programming,” *Energy Syst.*, 2023, doi: [10.1007/s12667-023-00591-2](https://doi.org/10.1007/s12667-023-00591-2).
- [24] N. Sugio, “Bit-Based Evaluation of Lightweight Block Ciphers SLIM, LBC-IoT, and SLA by Mixed Integer Linear Programming,” *IET Inf. Secur.*, vol. 2024, no. 1, 2024, doi: [10.1049/2024/1741613](https://doi.org/10.1049/2024/1741613).
- [25] E. M. Manuel, “Linear Programming Models for the Design of Energy-Efficient IoT Networks With Transmission Constraints,” *IEEE Trans. Green Commun. Netw.*, vol. 8, no. 1, pp. 391–401, 2024, doi: [10.1109/TGCN.2023.3305810](https://doi.org/10.1109/TGCN.2023.3305810).
- [26] N. Swatthong, “Optimal cloud orchestration model of containerized task scheduling strategy using integer linear programming: Case studies of `iotcloudserve@tein` project,” *Energies*, vol. 14, no. 15, 2021, doi: [10.3390/en14154536](https://doi.org/10.3390/en14154536).